



CERTIFICATE No. _____
(POLYPROPYLENE AND PROPYLENE COPOLYMERS)
TS 2211-074-05766563-2015 as amended 1

Grade 02003M1 **OKPD 2 Code** 20.16.51.190
Batch No. **Net weight**
Date of sampling
Test date
Designation of the regulatory documentation (RD),
according to which the sample was taken TS 2211-074-05766563-2015 as amended 1

Item No.	Name of the indicator	RD for test method	Norm	Analysis result
1	Melt flow rate (230 °C / 2.16 kg), g/10min	ASTMD 1238	from 0.2 to 0.5	
2	The spread of the melt flow rate within the batch1, %	TS 2211-074-05766563-2015, cl. 5.5	maximum 15	
3	Mass fraction of granules with a size of more than 6 to 8 mm and less than 1 mm, as well as stuck together, provided that no more than three granules stick together, %	TS 2211-074-05766563-2015, cl. 1.2	not more than 3	
4	Mass fraction of volatile substances, %	TS 2211-074-05766563-2015, cl. 5.6	not more than 0,09	
5	Resistance to thermo-oxidative aging at 150 °C as to formulation 229, hour	TS 2211-074-05766563-2015, cl. 5.9	minimum 2000	
6	Tensile yield point, MPa	ASTMD638	not less than 30	
7	Elongation at yield strength, %		not less than 14	
8	Elongation at break, %		not less than 200	
9	Modulus of flexibility, mPa	ASTMD790	not less than 1300	
10	Izod impact toughness of notched sample at 23 °C, J/m	ASTMD256	not less than 500	-
11	Izod impact toughness of notched sample at minus 20 °C, J/m		not less than 70	
12	Izod impact toughness of notched sample at minus 40 °C, J/m		not less than 40	

Note: 1) The indicator is determined by the calculation method.

Conclusion: the product meets TS 2211-074-05766563-2015, as amended 1.

Not subject to mandatory certification

The products are manufactured under the guidance of the Management Systems certified for compliance with the requirements: ISO 9001:2015 Certificate No. 31100600 QM15, ISO 140 01:2015 Certificate No. 31100600 UM15, BS OHSAS 1800 1:2007 Certificate No. 31100600 BSOH.

Scope of application: for non-pressure pipelines, pipeline parts, drainage and sewer pipes, profile extrusion products, sheets, plates, products in contact with food, toys.

Characteristics of fire and explosion hazard: pelletized baleen as per GOST 12.1.044 is related to the group of solid combustible materials with high smoke-producing capacity. When baleen heating, during the processing up to temperature up to 150 °C, the formation of products of volatile thermal destruction, which contain organic acids, carbonyl compounds, including formaldehyde, acetaldehyde, carbon oxide. Upon contact with an open fire, the baleen burns with a smoky flame without an explosion with the formation of a melt and the release of carbon dioxide, water vapor, unsaturated hydrocarbons and the above thermal destruction products. Air-borne dry dust of baleen is explosive; the particle friction results in accumulating the charge of static electricity.

Transportation rules: baleen is transported by all types of transport in covered vehicles in accordance with the rules of cargo transportation applicable to this type of transport. Baleen packed in bags, when loaded into containers according to GOST 15102 or GOST 20435, is transported in any means of transport. It is allowed, upon agreement with the consumer, to transport in bulk in railway cars and road pneumatic tanks.

Storage rules: baleen is stored in closed room while avoiding the exposure of direct sunlight at a distance of not less than 1 m from heating devices at a temperature not more than 30 °C and relative humidity not more than 80 %. Before opening, bags with polyethylene must be kept in the production room for at least 12 hours. It is allowed to store the baleen at the consumer's for up to 30 days in the outdoor areas installed metal containers for storage, excluding the ingress of moisture and contamination of the product.

Neutralization, disposal, and burial of wastes: waste unsuitable for recycling does not require neutralization, and is subject to removal to places agreed with the bodies of the Ministry of Civil Defense, Emergencies and Disaster Relief and the Federal Service for Supervision of Consumer Rights Protection and Human Welfare (Division of the Federal Service for Supervision of Consumers Protection and Welfare (Rospotrebnadzor).

Warranty period of storage: 3 years from the date of manufacture.

Chemical Analysis Laboratory Assistant of the 5th grade – production team leader

(power of attorney No. 1/19 dated 01.01.19)

L.S.

Certificate registration date